


 Cinderella® <small>Incineration Toilets</small>	 Cinderella® <small>Incineration Toilets</small>	 Cinderella® <small>Incineration Toilets</small>	INCINOLET <small>ELECTRIC INCINERATING TOILET</small>	 ECOJOHN®
<i>Incineration Toilet</i>	<i>Cinderella Freedom</i>	<i>Cinderella Travel</i>	<i>Cinderella Comfort</i>	<i>Incinolet</i>	<i>EcoJohn TinyJohn</i>
<i>Certifications</i>	<i>NSF / C-UL-US</i>	<i>C-UL-US</i>	<i>NSF / C-UL-US</i>	<i>C-UL-US</i>	<i>None</i>
<i>Warranty period</i>	<i>3 years</i>	<i>3 years</i>	<i>3 years</i>	<i>2 years</i>	<i>1 year</i>
<i>Can combustion chamber be opened during incineration</i>	<i>No</i>	<i>No</i>	<i>No</i>	<i>Yes</i>	<i>No</i>
<i>Temperature outside of the toilet</i>	<i>33°C</i>	<i>33°C</i>	<i>35°C</i>	<i>47°C</i>	<i>35°C</i>
<i>Where is air taken from?</i>	<i>Back</i>	<i>Back</i>	<i>Back</i>	<i>Grate on left side</i>	<i>Back</i>
<i>Volume of air moved?</i>	<i>67 cfm</i>	<i>55 cfm</i>	<i>76 cfm</i>	<i>147 cfm</i>	<i>71 cfm</i>
<i>dB level during operation</i>	<i>62 dB</i>	<i>65 dB</i>	<i>63 dB</i>	<i>72 dB</i>	<i>80 dB</i>
<i>Indicator to notify user to empty ash container?</i>	<i>Yes</i>	<i>Yes</i>	<i>Yes</i>	<i>No</i>	<i>Yes</i>
<i>Incineration time (Single use)</i>	<i>51 minutes</i>	<i>55 minutes</i>	<i>78 minutes</i>	<i>83 minutes</i>	<i>60 minutes</i>
<i>Energy consumption</i>	<i>Peak 1.2 amp @ 12V / ~200g propane</i>	<i>Peak 0.2 amp @ 12V / ~200g propane</i>	<i>Peak 8.2 amp @ 240V</i>	<i>Peak 14.5 amp @ 230V</i>	<i>Peak 1.3 amp @ 12V / ~200g propane</i>
<i>Incineration time (Heavy use)</i>	<i>2 hours 35 minutes</i>	<i>2 hours 37 minutes</i>	<i>2 hours 25 minutes</i>	<i>2 hours 45 minutes</i>	<i>Overcapacity</i>

All stats are based on an independent comparison of popular incineration toilets available in the North American market.